S ~ ۵ ш ~ Z

SWT 120 DXL13 DE PUMP Pumps range







Built around durability, our SWT Diesel trash pumps feature a silicon carbide seal and a unique conical cast iron impeller design and a quick-clean-out port for easy maintenance and long service life. They reduce wear from abrasive materials and can handle solid objects up to 31 mm in diameter. There's even a strainer to ensure nothing bigger gets through.

Serial equipment

- ✓ Self-priming
- Electric start
- Carbon mechanical seal
- ✓ Diesel 4-stroke engine
- ✓ Steel strainer, hose coupling and band

Optional equipment

- → Wheelbarrow kit (factory option): 4NC
- + Fire fighter hose coupling

		SWT 120 DXL13 DE
Pump type		Self-Priming
Suction Ø coupling	mm	100 (4")
Delivery Ø coupling	mm	100 (4")
Discharge flow	L/min	1750
Discharge flow	m³/h	105
Pressure	bar	2,5
Maximum total head	m	25
Discharge head	m	8
Solid size Ø (Ø of Hole of strainer)	mm	31
Mechanical seal		Ceramic carbon
Engine model		YANMAR - L48
Engine type		4 stroke Diesel
Fuel type		Diesel (Do not use domestic or heating oil)
Fuel tank capacity	L	13
Autonomy	h	10 h
Dimensions L x W x H	mm	840 x 530 x 729
Packaging dimensions L x W x H	mm	_
Dry weight	kg	112
Gross weight	kg	_

WORMS Entreprises

ZAC de Lamirault 39 rue de Lamirault 77090 Collégien FRANCE TEL. +33 (0) 1 64 76 29 67

FAX +33 (0) 1 64 76 29 99 export@wormsentreprises.com www.wormsentreprises.com